

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
31 December 2003 (31.12.2003)

PCT

(10) International Publication Number
WO 2004/000397 A1

(51) International Patent Classification⁷: **A61M 5/32**

(21) International Application Number:
PCT/GB2003/002689

(22) International Filing Date: 23 June 2003 (23.06.2003)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
02 14452.5 22 June 2002 (22.06.2002) GB
03 02393.4 3 February 2003 (03.02.2003) GB

(71) Applicant and

(72) Inventor: **LIVERSIDGE, Barry, Peter** [GB/GB]; The
Wick, Wick Road, Langham, Colchester, Essex CO4 5PE
(GB).

(74) Agents: **GILLAM, Francis, Cyril et al.**; Sanderson &
Co., 34 East Stockwell Street, Colchester, Essex CO1 1ST
(GB).

(81) Designated States (*national*): AE, AG, AL, AM, AT, AU,
AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU,
CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH,
GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC,
LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW,
MX, MZ, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC,
SD, SE, SG, SK, SL, TJ, TM, TN, TR, TT, TZ, UA, UG,
US, UZ, VC, VN, YU, ZA, ZM, ZW.


(84) Designated States (*regional*): ARIPO patent (GH, GM,
KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW),
Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM),
European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE,
ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO,
SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM,
GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Published:

— with international search report

For two-letter codes and other abbreviations, refer to the "Guid-
ance Notes on Codes and Abbreviations" appearing at the begin-
ning of each regular issue of the PCT Gazette.

(54) Title: MEDICAL NEEDLE ASSEMBLIES



(57) Abstract: A safety arrangement for a medical needle (15) has a support (14) for carrying the mount end of the needle, and a sleeve (16) slidably mounted on the support (14) for movement from an initial position to a retracted position and then back to a protecting position where the sleeve (16) covers the tip (21) of the needle (15). A spring (32) urges the sleeve towards its protecting position and a blocking member (23) projects forwardly from the support (14) and is movable between non-blocking and blocking positions. In the non-blocking position the sleeve (16) is free to slide from its initial position to its retracted position. On movement of the sleeve to its protecting position, the blocking member (23) moves to lie between the support (14) and sleeve (16) to prevent subsequent movement of the sleeve away from its protecting position. A control mechanism (27) releases the blocking member (23) so that it may move from its non-blocking position to its blocking position, the mechanism (27) being controlled by movement of the sleeve (16) from its initial position at least partway towards its retracted position.

WO 2004/000397 A1